

Reducing Energy Consumption with Passive Cooling



Ian Cathcart, RCDD

Technical Support Manager Chatsworth Products International.

11th October 2012






- Understanding Importance of Air Isolation
- Types of Air Isolated & Contained Solutions



<section-header><list-item><list-item><list-item><list-item><list-item>

Average Data Centre Power Allocation



Average power allocation for 12 benchmarked data centers (LBNL).



Mechanical Inefficiencies


Definition:


<u>Bypass Airflow</u> is when conditioned air is not getting to the intakes of the IT equipment

- 60% of the cool air cools the room but not the critical load except by recirculation
- Only 40% of cool air is supplied through cold aisle



With Bypass Airflow





Room Air Bypass and Re-Circulation

- Unsealed raised floor cable cutouts cause bypass airflow
- Cool Air bypassed floor tiles re-circulates around room







Mechanical Inefficiencies


<section-header>
Considerations
Ease of use?
Requires policing?
Particulates?
Retrofit-able?
Static dissipation of raised floor?

Practical limitations of under-floor cooling

- · Airflow through perforated floor tiles is limited
- Perforated floor tiles typically limited to 1189 CMH / 700 CFM Approx 9kW for Blades and 4.5 kW for standard box servers
- Floor grates typically limited to 2379 CMH / 1400 CFM Approx18kW for Blades and 9 kW for standard box servers



Hot Aisle / Cold Limitations




What Is The Target?

The latest ASHRAE recommended environmental envelope for Class 1 Electronics

	2004 Version	2008 Version
Low End Temperature	20°C (68 °F)	18°C (64.4 °F)
High End Temperature	25°C (77 °F)	27°C (80.6 °F)
Low End Moisture	40% RH	5.5°C DP (41.9 °F)
High End Moisture	55% RH	60% RH & 15°C DP (59
-		°F DP)





Do I have a Hot-Spot?

11 12 13 14 16 17 18 19 20 21 22 23 24 26 27 28 29 30 31 35 37 38 39 68 70 72 74 76 78 80 82 84 86 88 90 92 94 96




Strategically placed temperature strips can give a low cost visual reference

Use infrared thermometer to measure for hot spots – any point at air in-take over $27^{\circ}C$ (80.6°F).


BICSI Measure directly at server in-take




Typical Set Point Management?





Typical Set Point Management?



Typical Set Point Management?







Reducing Energy Consumption with Passive Cooling

- Understanding Importance of Air Isolation
- Types of Air Isolated Containment Solutions




Planning For Data Centre's

A change of thinking . . .



Why is the cabinet important?

The cabinet is the **architectural feature** in the data centre **that secures** the **isolation** between supply air and return air



Planning For New Data Centre's:




Water is 3467 times more efficient than air in removing heat



Water Cooled Cabinets

- Benefits
 - Cooling directly at the cabinet
 - Doesn't require air distribution underneath a raised floor
 - Can be scaled to kW of cabinet load

- Isolates hot air from cool air




Bicsi


Water Cooled Cabinets

- Negatives
- Complicated
- Coolant lines in data centre
- Multiplies the possible points of failure
- Lifespan on components = redundancy plan
- Costly
- Both cabinets & construction costs

- Operating costs
- Service








Cold Aisle Containment

11 .

Benefits

- 100% Utilization
- Provides uniform cool air to equipment
- Isolates hot air from cool air
- High Return Temperatures
- Low cost of ownership






Cold Aisle Containment

Negatives

- Redundancy planning (Thermal Mass)
- Room temperature is uncomfortable & air turbulence
- Must be installed in rows
- Dependant on raised floor




- 111


- Temperamental pressure level under floor and in CAC

 $: \prod_{i=1}^{n} \prod_{j=1}^{n} \prod_{i=1}^{n} \prod_{j=1}^{n} I_{j} :$



Cold Aisle Containment






Cold Aisle Containment



Hot Aisle Containment

Benefits

- 100% Utilization
- Higher Thermal Mass
- Comfortable Room
- Not dependant on raised floor
- High Return Temperatures






Hot Aisle Containment


11 .

Negatives


- Hot Aisle temperature is uncomfortable & air turbulence
- Must be installed in rows
- Ducting is required
- Must plan ahead
- Expensive











Chimney Cabinets


Negatives


- >1050 mm cabinet is required
- Return plenum is required for full isolation
- Light reduction between aisles




Chimney Cabinets

How does it look on a Raised Floor Plenum?







Chimney Cabinets











What Is the Best Containment?


DataCenter 2020: Hot-aisle and Cold Aisle Containment Efficiencies Reveal No Significant Differences

Copyright © 2011 Intel Corporation.

The DataCenter 2020 is a joint T-Systems and Intel data center test laboratory in the Munich-based Euroindustriepark.

www.datacenter2020.com





Thank You!

